3-M COMPANY -- SCOTCHKOTE ELECTRICAL COATING -- 5970-00-962-3335

========== Product Identification ==========

Product ID:SCOTCHKOTE ELECTRICAL COATING
MSDS Date:01/01/1985
FSC:5970
NIIN:00-962-3335
MSDS Number: BFZJM
=== Responsible Party ===
Company Name:3-M COMPANY
Address:3M CTR
City:ST PAUL
State:MN
ZIP:55144-1000
Country:US
Emergency Phone Num:800-854-0631
CAGE:GO802
=== Contractor Identification ===
Company Name:3-M COMPANY
Address:3M CTR 224-2S-25
Box:City:ST. PAUL
State:MN
ZIP:55144-1000
Country:US
Phone:612-733-1341
CAGE:GO802
Company Name:MINNESOTA MINING AND MFG CO INDUSTRIAL MINERALS DIV
Address:3M CTR
Box:City:SAINT PAUL
State:MN
ZIP:55144-1000
Country:US
Phone:612-737-4114
CAGE:94962

========== Composition/Information on Ingredients ==========

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 60%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 30%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

========== Hazards Identification ==========

Effects of Overexposure:VAPORS MAY IRRITATE EYES, NOSE & THROAT & CAUSE

NAUSEA, HEADACHES & NARCOSIS. EYE & SKIN IRRITANT.

========== First Aid Measures ==========

First Aid:EYES: FLUSH IMMEDIATELY WITH PLENTY OF WATER. SEEK MEDICAL ATTENTION. SKIN: WASH WITH SOAP & WATER. INHALATION: PROVIDE FRESH AIR.

========== Fire Fighting Measures ==========

Flash Point:25F (TOC)
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

========== Accidental Release Measures ==========

Spill Release Procedures:EXTINGUISH ALL IGNITION SOURCES. COLLECT SPILLED MATERIAL. CLEAN UP RESIDUE.

========== Handling and Storage ==========

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, & FLAMES. USE IN WELL-VENTILATED AREAS. AVOID PROLONGED OR REPEATED SKIN CONTACT.

========== Exposure Controls/Personal Protection ==========

Ventilation:LOCAL EXHAUST
Eye Protection:GOGGLES
Supplemental Safety and Health

========== Physical/Chemical Properties ==========

HCC:F2
Boiling Pt:=26.1C, 79.F
Spec Gravity:0.89
Solubility in Water:INSOLUBLE
Appearance and Odor:BROWN, VISCOUS LIQUID, KETONE ODOR
Percent Volatiles by Volume:81

========== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES

========== Disposal Considerations ==========

Waste Disposal Methods:INCINERATE PROPERLY. DO NOT LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.