

CHASE PRODUCTS CO -- ORGILL GRAY METAL PRIMER, 6-5697-1 -- 8010-00N092042

===== Product Identification =====

Product ID:ORGILL GRAY METAL PRIMER, 6-5697-1

MSDS Date:07/10/1995

FSC:8010

NIIN:00N092042

Status Code:A

MSDS Number: CJQFK

=== Responsible Party ===

Company Name:CHASE PRODUCTS CO

Box:70

City:MAYWOOD

State:IL

ZIP:60153

Country:US

Info Phone Num:708-865-1000

Emergency Phone Num:708-865-1000

Resp. Party Other MSDS Num.:428-2519

Preparer's Name:LAURA E RADEVSKI

CAGE:8D764

=== Contractor Identification ===

Company Name:CHASE PRODUCTS CO

Box:70

City:MAYWOOD

State:IL

ZIP:60153

Country:US

Phone:708-865-1000

CAGE:8D764

===== Composition/Information on Ingredients =====

Ingred Name:LIGHT ALIPHATIC SOLVENT NAPHTHA (PETROLEUM); (VM & P
NAPHTHA)

CAS:64742-89-8

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

Minumum % Wt:20.

Maxumum % Wt:25.

OSHA PEL:see Table Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ZINC PHOSPHATE

CAS:7779-90-0

RTECS #:TD0590000

Minumum % Wt:1.

Maxumum % Wt:5.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:ACETONE. BP: 133F,56.1C

CAS:67-64-1
 RTECS #:AL3150000
 Minimum % Wt:25.
 Maximum % Wt:30.
 OSHA PEL:2400 MG/M3;1000 PPM
 ACGIH TLV:1780 MG/M3;750 PPM
 ACGIH STEL:2380 MG/M3;1000 PPM
 EPA Rpt Qty:5000 LBS
 DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE OR ING 6
 CAS:74-98-6
 RTECS #:TX2275000
 OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:BUTANE (PROPELLANT BLEND)
 CAS:106-97-8
 RTECS #:EJ4200000
 OSHA PEL:800 PPM
 ACGIH TLV:1900 MG/M3;800 PPM

=====
 Hazards Identification
 =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
 Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
 Health Hazards Acute and Chronic:ACUTE: OVERINHALATION OF VAPOR OR MIST
 MAY CAUSE HEADACHE, DIZZINESS AND NAUSEA. PROLONGED CONTACT WITH
 SKIN MAY CAUSE IRRITATION. IRRITANT TO EYES ON CONTACT. TOLUENE
 APPEARS ON THE NAVY LISTING OF OCCUPATIONAL CHEMICAL REPRODUCTIVE
 HAZARDS. SEEK CONSULTATION FROM APPROPRIATE HEALTH PROFESSIONALS
 CONCERNING LATEST HAZARD LIST INFORMATION AND SAFE HANDLING AND
 EXPOSURE INFORMATION . CHRONIC: NOT KNOWN.
 Effects of Overexposure:SEE HEALTH HAZARDS.
 Medical Cond Aggravated by Exposure:NOT KNOWN.

=====
 First Aid Measures
 =====

First Aid:INGESTION: CALL MD IMMEDIATELY . INHALATION: IF OVERCOME BY
 VAPOR, MOVE VICTIM TO FRESH AIR. RESTORE RESPIRATION IF NECESSARY.
 SKIN & EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CO
 NSULT PHYSICIAN IF INJURY DEVELOPS.

=====
 Fire Fighting Measures
 =====

Flash Point:SEE EXTING MEDIA
 Extinguishing Media:FLAME PROJECTION: OVER 18 IN WITH FLASHBACK. DRY
 CHEMICAL, FOAM OR CARBON DIOXIDE.
 Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE
 EQUIPMENT . WATER SPRAY MAY BE USED TO COOL CANS IN VICINITY OF
 FIRE OR EXCESSIVE HEAT.
 Unusual Fire/Explosion Hazard:TEMPERATURES ABOVE 120F MAY CAUSE CANS TO
 BURST. AEROSOL FIRE PROTECTION LEVEL III (NFPA 30B).

=====
 Accidental Release Measures
 =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILATION TO AREA BEING
 TREATED. SOAK UP SPILL WITH CHEMICALLY INERT, ABSORBENT MATERIAL.

=====
 Handling and Storage
 =====

Handling and Storage Precautions:KEEP CAN CLOSED AND IN A COOL, DRY PLACE AWAY FROM HEAT AND OPEN FLAME.
 Other Precautions:KEEP OUT OF REACH OF CHILDREN. AVOID GETTING SPRAY INTO EYES.

=====
 Exposure Controls/Personal Protection
 =====

Respiratory Protection:NONE REQUIRED IF USED WITH ADEQUATE VENTILATION.
 NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .
 Ventilation:LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): OPTIONAL.
 Protective Gloves:RUBBER OR VINYL GLOVES.
 Eye Protection:ANSI APPROVED CHEMICAL WORKERS GOGGLES .
 Other Protective Equipment:EYE WASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA . APRON, IF DESIRED.
 Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USING THIS PRODUCT.
 Supplemental Safety and Health
 VOC%: 84.14.

=====
 Physical/Chemical Properties
 =====

Boiling Pt:=56.1C, 133.F
 B.P. Text:SEE INGRED 4
 Spec Gravity:0.93(H*20=1) (CONCENTRATE)
 Evaporation Rate & Reference:FASTER THAN BUTYL ACETATE
 Solubility in Water:INSOLUBLE
 Appearance and Odor:RED, HEAVY LIQUID WITH ODOR OF PAINT.

=====
 Stability and Reactivity Data
 =====

Stability Indicator/Materials to Avoid:YES
 AVOID HEAT, OPEN FLAME AND CONTACT WITH STRONG OXIDIZERS.
 Stability Condition to Avoid:TEMPERATURES ABOVE 120F.
 Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD GASES LIKE CARBON MONOXIDE AND CARBON DIOXIDE.
 Conditions to Avoid Polymerization:TEMPERATURES ABOVE 120F.

=====
 Disposal Considerations
 =====

Waste Disposal Methods:WRAP CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IT IN NON-INCINERATED TRASH ONLY. DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS .

=====
 MSDS Transport Information
 =====

Transport Information:ORM-D CONSUMER COMMODITY.

=====
 Regulatory Information
 =====

SARA Title III Information:TOLUENE, ZINC PHOSPHATE AND ACETATE ARE LISTED UNDER SARA SECTION 313.
 State Regulatory Information:CALIFORNIA'S PROPOSTION 65: "WARNING: THIS PRODUCT CONTAINS TOLUENE A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE REPRODUCTIVE TOXICITY".

=====
 Other Information
 =====

Disclaimer (provided with this information by the compiling agencies):
 This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.