

MATERIAL SAFETY DATA SHEET
Prepared according to 29 CFR 1910.1200

DATE PREPARED: May 1991
DATE REVISED: March 2009

PAGE 1
MSDS NO: 126

SECTION I - IDENTIFICATION

L&M CONSTRUCTION CHEMICALS, INC.
14851 CALHOUN ROAD
OMAHA, NE 68152

ASSISTANCE (CHEMTREC) 800-424-9300
EMERGENCY PHONE NO. 402-453-6600

ID NO.: N/Ap

PRODUCT
NAME: **SEAL HARD**

DOT CLASS: N/Ap

CHEMICAL
NAME: Chemical Hardener and Densifier

DOT SHIPPING
NAME: N/Ap

SECTION II - INGREDIENTS/IDENTITY INFORMATION

INGREDIENTS	OSHA PEL	ACGIH TLV	CAS	% wt
#1: Proprietary	Not Estab	Not Estab	Proprietary	< 50

Unlisted ingredients are not hazardous as defined in 29 CFR 1910.1200, and are considered the trade secret of L&M Construction Chemicals, Inc.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (F): 214-216
VAPOR PRESSURE (mm Hg): N/Ap
VAPOR DENSITY (AIR = 1): N/Ap
SOLUBILITY IN WATER: 100%
APPEARANCE: Colorless Turbid Liquid
ODOR: Odorless

SPECIFIC GRAVITY (H₂O = 1): 1.17
PERCENT VOLATILE BY VOLUME: 80-85
MELTING POINT: N/Ap
BULK DENSITY: 9.75 #/gal
PH INFORMATION: 10.5
EVAPORATION RATE: N/Ap

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, °F,: Non flammable
FLAMMABLE LIMITS - LEL: N/Ap UEL: N/Ap

EXTINGUISHING MEDIA: Non combustible product.

SPECIAL FIRE FIGHTING PROCEDURES: N/A

SECTION V - REACTIVITY DATA

STABILITY: unstable: stable: X

INCOMPATIBILITY (materials to avoid): Acidic materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Flammable hydrogen gas may be produced on prolonged contact with metals such as aluminum, tin, lead and zinc.

HAZARDOUS POLYMERIZATION: may occur: will not occur: X

SECTION VI - HEALTH HAZARD DATA**SEAL HARD**

POTENTIAL EFFECTS OF EXPOSURE (listed by primary routes of entry)

INHALATION: Exposure to mists or spray may cause coughing, sneezing or other symptoms of upper respiratory tract irritation. Severe exposure may result in lung tissue damage.

SKIN: Will cause severe irritation on continued contact.

INGESTION: Irritation to mucous membranes of the mouth, throat, esophagus and stomach.

EYE CONTACT: Can cause severe irritation if not treated.

EMERGENCY & FIRST AID PROCEDURES

INHALATION: If symptoms are present, get person out of area to fresh air. Seek medical attention.

SKIN: Wash with plenty of water for at least 15 minutes. Remove soiled clothing and footwear. Wash clothing before reuse. Footwear should be cleaned before reuse. Seek medical attention if symptoms are present.

INGESTION: Never give anything by mouth to an unconscious person. If swallowed, do not induce vomiting. Give large quantities of water or milk, if available. If vomiting occurs spontaneously, keep airway clear. Seek medical attention immediately.

EYE CONTACT: Object is to flush material out immediately, then seek medical attention. Immediately flush eyes with large amounts of water for several minutes holding lids apart to ensure flushing of the entire surface. Washing eyes 15 minutes is essential. Seek medical attention.

CARCINOGENICITY OSHA: NO NTP: NO IARC: NO

SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: If material is spilled or released, contain liquids and prevent discharges to streams or sewer systems.

WASTE DISPOSAL METHOD: Clean up action should be carefully planned and executed. Shipment, storage, and/or disposal of waste materials are regulated and action to handle spilled or released materials must meet the applicable rule. If any questions exist, contact the appropriate agencies.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: Shower and eyewash facilities should be accessible.

OTHER PRECAUTIONS: Can etch glass if not promptly removed. Floors may become slippery when wet with Seal Hard.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Use local exhaust ventilation where mists or spray may be generated.

VENTILATION

LOCAL EXHAUST: Where mists or spray may be generated

PROTECTIVE GLOVES: Standard work gloves

EYE PROTECTION: Face shield or chemical goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Standard work clothing. Standard work shoes.

WORK/HYGIENIC PRACTICES: Shower and eyewash facilities should be accessible. Wash contaminated clothing and dry before reuse.

END OF MSDS