



## Sikadur 31 Normal/Rapid Part A

Date of issue - 01/07/2002.

SKD31A

**PRODUCT AND COMPANY IDENTIFICATION**

**Product Code** SKD31A  
**Product Name** Sikadur 31 Normal/Rapid Part A  
**Product Description** Two component thixotropic adhesive based on epoxy resin.  
**Manufacturer/Supplier** Sika Limited  
Watchmead  
Welwyn Garden City  
Hertfordshire.  
AL7 1BQ  
tel. 01707 394444  
Fax. 01707 329129

**COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

Component		Concentration	Classification	Risk Phrases
1) Epoxy resin ( No.Av. mol.wt. < 700)	25068-38-6	25.00% - 50.00%	Xi, N	R36/38, R43, R51/53
2) 1,4-bis(2,3 epoxypropoxy)butane)	2425-79-8	2.50% - 10.00%	Xn	R20/21, R36/38, R43, R52/53
3) Nonyl Phenol	25154-52-3	1.00% - 2.50%	C, N	R22, R34, R50/53

**HAZARD IDENTIFICATION**

**Main Hazards** Irritating to eyes and skin.  
May cause sensitisation by skin contact.  
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**FIRST AID MEASURES**

**Eye Contact** Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.

**Skin Contact** Wipe off as much as possible with a clean dry cloth.  
Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent).  
Solvents should not be used to clean skin because they may increase the penetration of the material.  
Obtain medical attention if blistering occurs or redness persists.

**Ingestion** Wash out mouth with water. Obtain medical attention.

**Inhalation** Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

**FIRE FIGHTING MEASURES**

**Extinguishing Media** Not readily combustible. Use foam, dry chemical or carbon dioxide.

**Extinguishing Media - Not suitable** Do not use water jet.

**Special Hazards of Product** Combustion will produce smoke, carbon dioxide and carbon monoxide.

**Protective Equipment for Fire-Fighting** Wear full protective clothing and self-contained breathing apparatus.

**ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Wear appropriate protective clothing.

**Environmental Precautions and  
Clean-up Methods  
Spillages**

Try to prevent the material from entering drains or water courses.

Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

**HANDLING AND STORAGE****Handling**

Exposure by inhalation or skin contact should be minimised by good Industrial Hygienic practices.

Avoid contact with eyes, skin and clothing.

Use in well ventilated area.

**Storage**

Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

**EXPOSURE CONTROLS/PERSONAL PROTECTION****Engineering Control Measures**

Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

**Respiratory Protection**

Respiratory protection not normally required.

**Hand Protection**

Wear suitable impervious gloves. (butyl / nitrile type)

**Eye Protection**

Wear safety glasses if risks of accidental contamination are possible during application.

**PHYSICAL AND CHEMICAL PROPERTIES****Physical State**

Paste.

**Color**

Off-white.

**Odor**

Characteristic.

**pH**

Not applicable.

**Flash Point °C**

&gt; 100

**Solubility - Water**

Insoluble.

**Density (kg/m<sup>3</sup>)**

Approx. 1400 - 1500 at 20 °C.

**Viscosity ( at 20°C )**

Thixotropic paste

**STABILITY AND REACTIVITY****Stability**

Stable under normal conditions.

**Hazardous Decomposition Products**

Combustion will generate: oxides of carbon. acrid smoke and irritating fumes.

**TOXICOLOGICAL INFORMATION****Acute toxicity**

Low order of acute toxicity.

**Eye irritation**

Irritating to the eyes.

**Skin irritation**

Frequent or prolonged skin contact may cause some local short term skin irritation.

**Sensitization - Skin**

The low molecular weight epoxy resin is a potential skin sensitiser. The possibility of allergic sensitisation should be considered.

**ECOLOGICAL INFORMATION**

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


**DISPOSAL**

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

**TRANSPORT INFORMATION**

<i>UN : UN number</i>	3082
<i>UN : Packing Group</i>	3
<i>ADR/RID Substance Identification Number</i>	3082
<i>ADR/RID Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. contains Epoxy Resin
<i>ADR/RID Class</i>	9
<i>ADR/RID Item Number</i>	11 (c)
<i>IMDG : Proper shipping name</i>	Environmentally hazardous substance, liquid, N.O.S. contains Epoxy Resin
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	9
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

**REGULATORY INFORMATION**

<i>Label Requirements</i>	Irritant, Dangerous for the environment 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with eyes. Wear suitable gloves.  Contains epoxy constituents. See information supplied by the manufacturer.

**OTHER INFORMATION**

<i>First Issue Date</i>	28.09.1994
<i>Revisions Highlighted</i>	Composition and Information on Ingredients Physical and Chemical Properties



## SAFETY DATA SHEET

### Sikadur 31 Normal/Rapid Part A

Date of issue - 01/07/2002.

SKD31A

---

#### ***Uses and Restrictions***

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

#### ***UK Legislation***

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.  
Chemicals (Hazard Information and Packaging) Regulations, 2002.  
SI 1999/437: The Control of Substances Hazardous to Health Regulations  
SI No. 972/1996: The Special Waste Regulations 1996  
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

#### ***UK Guidance Publications***

Approved Code of Practice - Management of Health and Safety at Work, HSE.  
General Approved Code of Practice to COSHH Regulations, HSE.

#### ***Footnote***

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKD31B
<b>Product Name</b>	Sikadur 31 Normal Part B
<b>Product Description</b>	Two component thixotropic adhesive based on epoxy resin.
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients ( Europe )

<b>Component</b>		<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
1) Trimethylhexamethylene diamine	25620-58-0	25.00% - 50.00%	C	R22, R34, R43, R52/53

**HAZARD IDENTIFICATION**

<b>Main Hazards</b>	Harmful if swallowed. Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

**FIRST AID MEASURES**

<b>Eye Contact</b>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention urgently.
<b>Skin Contact</b>	Wipe off as much as possible with a clean dry cloth. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material. Contaminated clothing should be washed or dry-cleaned before re-use.
<b>Ingestion</b>	Do not induce vomiting. Obtain medical attention.
<b>Inhalation</b>	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

**FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<b>Extinguishing Media - Not suitable</b>	Do not use water jet.
<b>Special Hazards of Product</b>	Thermal decomposition or burning may release oxides of carbon, nitrogen and other toxic gases and vapours.
<b>Protective Equipment for Fire-Fighting</b>	Wear full protective clothing and self-contained breathing apparatus.

**ACCIDENTAL RELEASE MEASURES**

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

**HANDLING AND STORAGE**

<i>Handling</i>	Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices. Avoid contact with eyes, skin and clothing. Mix in a well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

**EXPOSURE CONTROLS/PERSONAL PROTECTION**

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

**PHYSICAL AND CHEMICAL PROPERTIES**

<i>Physical State</i>	Paste.
<i>Color</i>	Grey.
<i>Odor</i>	Amine like.
<i>pH</i>	Approx. 11 ( 10% in water)
<i>Flash Point °C</i>	Exceeds 100.
<i>Solubility - Water</i>	Partially soluble.
<i>Density (kg/m<sup>3</sup>)</i>	Approx. 1500
<i>Viscosity ( at 20°C )</i>	Thixotropic paste

**STABILITY AND REACTIVITY**

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: ammonia. oxides of carbon. oxides of nitrogen. acrid smoke and irritating fumes.

**TOXICOLOGICAL INFORMATION**

<i>Acute toxicity</i>	Low order of acute toxicity
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.
<i>Sensitization - Skin</i>	The possibility of allergic sensitisation should be considered



**SAFETY DATA SHEET**  
**Sikadur 31 Normal Part B**

Date of issue - 23/05/2002.

SKD31B

**ECOLOGICAL INFORMATION**

<i>Mobility</i>	The product is sparingly soluble in water.
<i>Persistence/degradability</i>	The rate of biodegradation will be governed by the low water solubility.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


**DISPOSAL**

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

**TRANSPORT INFORMATION**

<i>UN : UN number</i>	1759
<i>UN : Proper shipping name</i>	Corrosive solid, n.o.s. contains Trimethylhexamethylenediamine
<i>UN : Class</i>	8
<i>UN : Packing Group</i>	3
<i>ADR/RID Substance Identification Number</i>	1759
<i>ADR/RID Proper shipping name</i>	Corrosive solid, n.o.s. contains Trimethylhexamethylenediamine
<i>ADR/RID Class</i>	8
<i>ADR/RID Item Number</i>	65°( c )
<i>ADR/RID Hazard Identification Number</i>	88
<i>IMDG : Proper shipping name</i>	Corrosive solid, N.O.S. contains Trimethylhexamethylenediamine
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	8
<i>IMDG : Ems Number</i>	8-06
<i>IATA : Proper shipping name</i>	Corrosive solid, N.O.S. contains Trimethylhexamethylenediamine
<i>IATA : Packing Group</i>	3
<i>IATA : Class</i>	8

**REGULATORY INFORMATION**

<i>Label Requirements</i>	Corrosive 
<i>Risk Phrases</i>	Harmful if swallowed. Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Wear suitable protective clothing, gloves and eye/face protection.



**SAFETY DATA SHEET**  
**Sikadur 31 Normal Part B**

Date of issue - 23/05/2002.

SKD31B

**OTHER INFORMATION**

***First Issue Date***

28.09.1994

***Revisions Highlighted***

Hazards Identification  
Toxicological Information  
Transport Information  
Regulatory Information

***Uses and Restrictions***

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

***UK Legislation***

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.  
Chemicals (Hazard Information and Packaging) Regulations, 2002.  
SI 1999/437: The Control of Substances Hazardous to Health Regulations  
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.  
SI No. 972/1996: The Special Waste Regulations 1996

***UK Guidance Publications***

General Approved Code of Practice to COSHH Regulations, HSE.

***Footnote***

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.